

Primo 40 Aluminium Frame Glass Door

Primo 40 minibars have been quality engineered with generous internal space, simple and stylish design, low energy consumption and silent absorption technology. It's a great value for your hotel.

Standard Features

- Stocking capacity of up to 38 facings
- Removable shelving for easy cleaning
- Thermal insulation manufactured with cyclopentane
- Fully automatic defrost and easily adjustable thermostat
- Strong door hinge easily convert left to right
- All-round magnetic seals to keep the door perfectly shut
- Integrated door handle
- Lock (can be deactivated)
- Internal LED lighting
- Low energy consumption
- Advanced silent absorption cooling technology



Aluminium Frame Glass Door



Technical Specifications

	Primo 40 AFGD
Capacity (liters / cubic feet)	35.4L / 1.25Cu.Ft
Dimensions HxWxD (inches) (mm)	20.5 x 15.8 x 18.7 520 x 400 x 475
Door Options	Aluminium Frame Glass Door
Door Hinge	Universal
Shelves / Door Racks*	1 / 0*
Watts (W)	65
Voltage (V) / Frequency	110V / 60Hz 220V / 50Hz
Amps	0.56
Energy Consumption**	0.80 kWh/24 hr**
Gross Weight (lbs / kgs)	42.8 / 19.4
Net Weight (lbs / kgs)	40 / 18.1
Noise Level (dB)	0 dB
Certification	CCC/CB/CETL/CE/GS/RoHS/UL/CSA ISO 9001 2008/ISO 14001 2004

* No door racks available on glass doors
 ** Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.

Ventilation

A minimum opening of 31 in² (200 cm²) for Intake, Shelf Cutout and Exhaust is required for proper ventilation.

