

Primo 42d Solid Black Drawer

Primo 42d Drawer minibars have been quality engineered with generous internal space, simple and stylish design, low energy consumption and silent absorption technology. It's a great value for your hotel.

Standard Features

- Stocking capacity of up to 29 facings
- Transparent product display racks
- Removable shelving for easy cleaning
- Thermal insulation manufactured with cyclopentane
- Fully automatic defrost and easily adjustable thermostat
- Strong door slides
- Customized front panel to integrate with design
- All-round magnetic seals to keep the door perfectly shut
- Integrated door handle
- Lock (can be deactivated)
- Low energy consumption
- Advanced silent absorption cooling technology
- White or black interior options available

Technical Specifications

	Primo 42d SBD
Capacity (liters / cubic feet)	42L / 1.48Cu.Ft
Dimensions HxWxD (inches)* (mm)	16.5 x 21.75 x 19.5* 418 x 550 x 490
Door Options	Solid Black Drawer
Door Hinge	Drawer
Shelves	2
Watts (W)	70
Voltage (V) / Frequency	110V / 60Hz 220V / 50Hz
Amps	0.60
Energy Consumption**	0.80 kWh/24 hr**
Gross Weight (lbs / kgs)	56.2 / 25.5
Net Weight (lbs / kgs)	50.4 / 22.8
Noise Level (dB)	0 dB
Certification	CCC/CB/CETL/CE/GS/RoHS/UL/CSA ISO 9001 2008/ISO 14001 2004

*Add 0.91 inches (23 mm) to the depth of the PRIMO 42D for handle
 **Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.



Solid Black Drawer

Ventilation

A minimum opening of 31 in² (200 cm²) for Intake, Shelf Cutout and Exhaust is required for proper ventilation.

